



› PRINT › COPY › SCAN › FAX

TASKalfa 7002i

BLACK & WHITE
MULTIFUNCTIONAL SYSTEM

POWERFUL PERFORMANCE... CONNECT AND COLLABORATE.



The TASKalfa 7002i is an advanced Black-and-White MFP that offers the best of all worlds – outstanding ease of use, extraordinary image quality, fast throughput and exceptional durability. This versatile system is ideal for busy workgroups that require the flexibility to communicate in hardcopy and digital form. Print at up to 70 pages per minute. Scan at up to 220 images per minute. To further streamline processes, the customizable TASKalfa 7002i can be equipped with added paper drawers, professional finisher and integrated plug-and-play Kyocera business applications. Combined with ultra-reliability and long-life technology, Kyocera takes the end-user experience, and your business, to another level.

- › Crisp Black-and-White Output up to 70 Pages per Minute
- › Exceptional Print Quality up to 1200 dpi
- › Standard 4,150-sheet Paper Capacity, Expandable to 7,650 Sheets

- › Flexible Media Support and Paper Sizes up to 12" x 48"
- › Customizable 9" Color Touch Screen with Tablet-like Home Screen
- › Advanced Finishing Options for Professional Output, including a 4,000-sheet External Finisher and Optional Booklet Folding
- › Efficient High-speed Color Scanning up to 220 ipm
- › Standard USB Host Interface for On-the-Go Printing and Scanning
- › Convenient Wireless Printing and Scanning
- › Apple AirPrint®, Google Cloud Print™ and KYOCERA Mobile Print Compatible for Anytime, Anywhere Connectivity
- › Standard Near Field Communication (NFC) for Android and Wi-Fi Direct Provides Added Smart Device Convenience
- › KYOCERA Fleet Services, a secure cloud-based monitoring system, optimizes device uptime and reduces costs

TASKalfa 7002i

BASIC SPECIFICATIONS

Configuration: Black and White Multifunctional System – Print/Scan/Copy/Optional Fax

Pages Per Minute:

Letter: 70 ppm, Legal: 42 ppm, Ledger: 35 ppm, 12" x 18": 35 ppm (print only)

Warm Up Time: 30 Seconds or Less (Power On)

First Page Out:

Copy: 5.2 Seconds or Less

Print: 5.8 Seconds or Less

Display: 9" Color Touch Screen Control Panel

Resolution: 600 x 600 dpi; 9600 dpi x 600 dpi; 1200 x 1200 dpi

Memory / Hard Disk Drive: 4.5 GB RAM / 8 GB SSD / 320 GB HDD Standard

Duplex: Standard Stackless Duplex Supports Statement to 12" x 18", 14 lb Bond – 166 lb Index (52 – 300gsm)

Standard Output Tray: Statement – 12" x 18" / 270 Sheets; up to 12" x 48" Banner (Single Sheet)

Electrical Requirements: 120V, 60Hz, 12A; 220-240V, 50Hz, 7.2A

Typical Electricity Consumption (TEC): 120V: 4.7 kWh/week; 220V: 4.5 kWh/week

Dimensions: 26.97" W x 31.10" D x 41.45" H

Weight: 330 lbs

Maximum Monthly Duty Cycle: 400,000 Pages per Month

PAPER SUPPLY

Standard Paper Sources: Dual 500 Sheet Trays, Dual 1,500 Sheet Trays, 150 Sheet MPT, Auto Selection / Switching

Optional Paper Sources: Dual 500 Sheet Trays (PF-730[B]), Dual 1,500 Sheet Trays (PF-740[B]); Side LCT: 3,000 Sheet Capacity Tray (PF-7120); 500 Sheet Multi-Media Paper Feeder (PF-7130)

Paper Capacity: Standard: 4,150 Sheets; Maximum: 7,650 Sheets

Paper Size:

Tray 1 – 5.5" x 8.5" – 12" x 18" (Statement to 12" x 18"); Tray 2 – 5.5" x 8.5" – 12" x 18", Custom Size; PF-7100: 5.5" x 8.5" – 12" x 18"; PF-7100: 5.5" x 8.5" – 12" x 18"; PF-7200: 8.5" x 11" – 12" x 18"; MPT: 5.5" x 8.5" – 12" x 18" (Multiple Sheets); up to 12" x 48" Banner (Single Sheet)

Paper Weight: Trays / MPT: 16 lb Bond – 166 lb Index (60 – 300gsm)

Input Materials: Standard/Optional Drawer: Plain Paper, Bond Paper, Recycled Paper, Envelopes; MPT: Plain Paper, Bond Paper, Recycled Paper, Cardstock, Transparencies, Labels, Envelopes

SECURITY SPECIFICATIONS

Standard: Local Authentication, Network Authentication (IPsec, HTTPS, LDAP over SSL, SNMPv3); Secure Print (IPP over SSL); Scan to Email (POP3/SMT over SSL); Scan to FTP (FTP over SSL); Scan to SMB/PC/USB; FTP over SSL

Optional: Data Security Kit (E): HDD Overwrite Mode, HDD Data Encryption

PRINT SPECIFICATIONS

Standard Controller: Freescale QorIQ T1042 (Dual Core) / 1.2GHz

PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL / PCL5), KPDL3 (PS3), PDF, OpenXPS, XPS, PPML; Optional (UG-34): IBM ProPrinter, Line Printer, LQ-850

Print Resolution: Up to 1200 x 1200 dpi

Fonts: 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap

OS Compatibility: Windows: XP/Vista/7/8/8.1/10/Server 2003/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2; Novell NetWare 3.x/4.x/5.x/6.x; Mac OS 10.x; AirPrint Enabled; Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)

Mobile Printing: Apple AirPrint®, Google Cloud Print™, KYOCERA Mobile Print

Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB Host Interfaces, 2 Expansion Slots, Wireless LAN (communication distance 98.5 feet)

Optional: 10/100/1000BaseTX (IB-50 for Dual NIC), IEEE 802.11b/g/n IB-51 for Wireless LAN Interface (communication distance 328.1 feet)

Network Print and Supported Protocols: TCP/IP, FTP, LPR, NetBEUI, IPv4, IPv6, IPsec, SSL, HTTP, LPD, IPP, RawPort, LLTD, SNMP, DHCP, SMTP, POP3, DNS, SNMPv1/v2, WSD Scan/Print
Drivers: KX Driver, KX (XPS) Driver, PCL Mini Driver, KPDL Mini Driver, Network Fax Driver, TWAIN Driver, WIA Driver, Status Monitor, Novell NDPS, Common Profile, Output to PDF, Security Watermark, Color Optimizer, Linux SANE Driver, Linux Driver, Mac Driver, Windows Inbox Driver, KX PRESCRIBE Macro Generator
Utilities: KYOCERA Net Direct Print, File Management Utility, KYOCERA Print Center, KYOCERA Net Admin, KYOCERA Net Viewer, Quick Setup, KYOCERA Net Manager(Pro), KYOCERA Net Manager (Basic), ID Register, Software Management Service, Upgrade Studio, Web Package Builder, Web Package Maker, Removal Tool, Wi-Fi Setup Tool

SCAN SPECIFICATIONS

Scan Type: Color and Black & White Scanner

Scan Resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi

File Formats: TIFF (MMR compression), PDF (MMR compression), PDF (high compression), OpenXPS, XPS, JPEG

PDF Extension: Searchable PDF (OCR)

Scan Speeds (mono/color, @300 dpi):

Simplex: 120 ipm B&W / Color

Duplex: 220 ipm B&W / Color

Connectivity / Supported Protocols: 10/100/1000BaseTX, TCP/IP, Hi-Speed USB 2.0

Scanning Functions: Scan to Folder (SMB), Scan to Email, Scan to FTP, Scan to FTP over SSL, Scan to USB, WSD Scan, TWAIN Scan

Original Size: Through DP: Statement to Ledger (5.5" x 8.5" – 11" x 17"); Glass: Up to 11" x 17"

Drivers: TWAIN Driver / KM-WSDL / WSD

COPY SPECIFICATIONS

Copy Resolution: 600 x 600 dpi

Image Mode: Text, Photo, Text/Photo, Graphic/Map

Continuous Copy: 1 – 9,999 / Auto Reset to 1

Additional Features: Auto Magnification, Auto Paper Select, Auto Start, Auto Drawer Change, Interrupt Copy, Positive / Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, Page Number, Form Overlay, XY Zoom, Prevent Bleed Through, Text Stamp, Bates Stamp, Blank Page Skip

Job Management: 1,000 Department Codes, Job Programs, Job Build, Shortcut Keys, Repeat Copy

Color Adjustment: One Touch, Hue, Auto Exposure, Sharpness

Magnification / Zoom: Full Size, 4 Reduction, 4 Enlargement Preset Ratios, 25 – 400% in 1% Increments

Document Box: Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

STANDARD DOCUMENT PROCESSOR

Type / Capacity: Dual Scan Document Processor / 270 Sheets

Acceptable Originals: 5.5" x 8.5" – 11" x 17"

Acceptable Weights:

Simplex: 16 lb Bond – 68 lb Index (60 – 256gsm)

Duplex: 13 lb – 32 lb Bond (50 – 120gsm)

OPTIONAL FAX SPECIFICATIONS

Fax Type: Fax System 12

Compatibility / Data Compression: G3 Fax / MMR, MR, MH, JBIG

Transmission Speed / Modem Speed: Less than 3 Seconds per Page / 33.6 Kbps

Fax Memory: Standard 170 MB

Driver: Network Fax Driver

Fax Functions: Network Fax, Duplex Transmission and Reception, Encrypted Transmission and Reception, Polling Transmission and Reception, Broadcast

OPTIONAL 4,000 SHEET FINISHER DF-7110¹

Stack / Staple Capacity: Main Tray (A): 4,000 Sheets; Sub Tray (B): 200 Sheets / 65 Sheets (up to 24 lb Bond [90gsm])

Paper Size: 5.5" x 8.5" – 12" x 18"

Paper Weight: 14 lb Bond – 166 lb Index (52 – 300gsm)

Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 8.5" x 11" – 12" x 18"; 14 lb Bond – 166 lb Index (52 – 300gsm)

Dimensions: 23.91" W x 26.32" D x 41.78" H

Optional Booklet Folder / Tri-fold Unit²: BF-730 Booklet Folder supports 8.5" x 11", 8.5" x 14", 11" x 17"; Fold booklet staple: 16 lb – 24 lb Bond (60 – 90gsm) 16 sheets; 25 lb – 28 lb Bond (91 – 105gsm) 13 sheets; Fold booklet no staple: 16 lb – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets; 32 lb Bond – 110 lb Cover (121 – 256gsm) 1 sheet; Tri-fold Unit supports 8.5" x 11" only: 16 lb – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets; 16 lb – 28 lb Bond (60 – 105gsm) 1 sheet

Optional Multi-bin Mailbox³: MT-730(B) Includes 7 Trays; Supports 16 lb Bond – 90 lb Index (60 – 163gsm); Stack Capacity per Bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"

ADDITIONAL OPTIONS

Banner Guide (A), Internet Fax Kit (A), Card Authentication Kit (B), Gigabit NIC (IB-50), IEEE 802.11b/g/n (IB-51), ThinPrint (UG-33), Emulation (UG-34), Keyboard Holder 10, Key Counter, Key Counter Attachment Kit, Copy Tray (D), Data Security Kit (E), Numeric Keypad (NK-7110)

¹ Requires PF-7130

² Only 1 Output Option can be installed

³ Requires DF-7110

ONLY FROM KYOCERA

KYOCERA Document Solutions is a global leader in the digital imaging industry, with an award-winning line of document solutions that consistently set the standard for high performance, superior image quality, enhanced workflow applications, ease-of-use and durability.

Looking to streamline your document workflow? Kyocera offers a robust portfolio of business applications that seamlessly and securely integrate with our MFPs. To learn more about which business applications are right for your business, visit the Solutions section on our website.

Specifications and design are subject to change without notice.

For the latest on connectivity, please visit www.kyoceradocumentsolutions.com/us.

MAC and AirPrint are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc.

TASKalfa, PRESCRIBE, KX Driver, and Command Center RX are the trademarks of the Kyocera Companies.

All other trademarks are the property of their respective owners.



KYOCERA Document Solutions America, Inc.
Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
©2017 KYOCERA Document Solutions America, Inc.
IC# 855D400489

 **KYOCERA**
Document Solutions